



## **BOOST 2+ MAX** **LARGE CAPACITY CENTRIFUGE**

Part # 00-263-009-000

Satisfy your lab's most diverse processing requirements with the BOOST 2+ Max. This general-purpose laboratory centrifuge may also be used to spin approved containers with biologics, some chemicals, and environmental samples.

### **Fully Customizable**

The BOOST 2+ Max offers a variety of extensive customization options. Personalize the front panel label and LED lid lights to match your unique branding, or pre-program custom RPM and g-force settings to meet your preferred processing specifications.

### **Spins Your Cycles**

Program and recall up to 10 preset cycles with the BOOST 2+ Max's backlit digital display. Can be set to run preset cycles only, or may be locked to just one preset cycle if desired.

### **Fits Your Tubes**

Experience unmatched convenience with the BOOST 2+ Max's unique insert system. Simply select the correct adapter for each tube size and switch them out as needed to spin every tube.

### **Safe and Durable**

Enjoy years of worry-free operation with BOOST's imbalance protection and shatterproof lid, which can only be opened when the rotor is stopped - even if the unit loses power. Rigorous electrical testing ensures our centrifuges meet hospital equipment safety standards.

### **A Great Value**

Unbeatable quality and flexibility for any budget. Each BOOST 2+ Max centrifuge is ready to run with swing-out horizontal rotor, buckets, and 2-year warranty included in the affordable price.

### **Unique Rotor Design**

Our patented high-volume horizontal rotor and custom adapters designed in-house ensure a perfect fit for any tube.



<b>Applications</b>	<b>Max Speed</b>	<b>Max Capacity</b>	<b>Included</b>	<b>Warranty</b>
Variable Tube Sizes Custom Disposables	3200 RPM 1800 xg RCF	2 x Up to 3.6 x 5.4 in (91 x 137 mm) or 330 grams	Horizontal Rotor 2 x BOOST 2+ Max Buckets	2 years Extended warranty options available

**Designed, built, and supported in the USA**

# BOOST 2+ Max



LED lid lights indicate cycle status: ready, running, done

Easily spin a wide variety of tubes with swappable inserts

QR code for easy access to support videos, manuals, and more

View RPM and remaining spin time on the digital display

Program and name your custom validated cycles  
Store up to 10 preset cycles

## Free 30-Day Evaluation (U.S. Only)

### Part Numbers

Part Numbers	
	Centrifuge 00-263-009-000
Included	BOOST 2+ Max Buckets (2 qty) (Up to diameter of 3.6 in / 91.4 mm) (Up to length of 5.4 in / 137.2 mm) 03-1-0007-0162
Optional	1 yr Warranty Extension 03-0-0007-0003
	2 yr Warranty Extension 03-0-0007-0004
	3 yr Warranty Extension 03-0-0007-0005

### Specifications

Sound Level	67 dBA
Max Speed RPM	3200 RPM
Max G-Force	1800 xg
Dimensions (W x D x H)	15 x 18 x 10 in 38.1 x 45.7 x 25.4 cm
Weight	37 lbs (17.69 kg)
Power	100-240 V – 50/60 Hz
Resting Tube Angle	10° (from vertical)
Tube Spin Angle	90° (horizontal)
Maximum Load	330 g per bucket



druckerdiagnostics.com  
sales@druckerdiagnostics.com

+1-866-265-1486 (U.S. only)  
+1-814-692-7661