


**DASH Centrifuges**  
**High Performance STAT Processing**

Model	Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	Up to 13 x 75 mm or 5 mL			Dimensions (W x D x H)
DASH Apex 4 00-053-009-000	Fixed Angle	2-Button, 3-Setting	30 sec / 8500 RPM / 4440 xg 2 min / 8500 RPM / 4440 xg 3 min / 8500 RPM / 4440 xg	8500 / 4440	4			7 x 7 x 7 in 17.8 x 17.8 x 17.8 cm
Model	Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	Up to 16 x 100 mm or 10 mL	Up to 16 x 125 mm or 15 mL	50 mL	Dimensions (W x D x H)
DASH Coag 00-676-009-001	Fixed Angle	2-Button, 3-Setting	2 min / 6600 RPM / 4400 xg 3 min / 6600 RPM / 4400 xg 5 min / 5200 RPM / 2700 xg	6600 / 4400	12	-	-	12 x 14 x 9 in 30.5 x 35.6 x 22.9 cm
DASH Apex 6 00-076-009-004	Horizontal	2-Button, 3-Setting	3 min / 5300 RPM / 4000 xg 5 min / 5300 RPM / 4000 xg 7 min / 3800 RPM / 2000 xg	5300 / 4000	6	-	-	12 x 14 x 9 in 30.5 x 35.6 x 22.9 cm
DASH Flex 6 00-176-009-000	Horizontal	Digital, 10-Setting	3 min / 5300 RPM / 4000 xg 5 min / 5300 RPM / 4000 xg 10 min / 3800 RPM / 2000 xg	5400 / 4150	6	-	-	12 x 14 x 9 in 30.5 x 35.6 x 22.9 cm
DASH Apex 12 00-083-009-003	Horizontal	2-Button, 3-Setting	3 min / 5200 RPM / 4000 xg 5 min / 5200 RPM / 4000 xg 7 min / 3600 RPM / 2000 xg	5200 / 4000	12	-	-	13 x 15 x 9 in 33 x 38.1 x 22.9 cm
DASH Flex 12 00-183-009-000	Horizontal	Digital, 10-Setting	3 min / 5200 RPM / 4000 xg 5 min / 5200 RPM / 4000 xg 7 min / 3600 RPM / 2000 xg	5200 / 4000	12	-	-	13 x 15 x 9 in 33 x 38.1 x 22.9 cm
DASH Apex 24 00-084-009-005	Horizontal	2-Button, 3-Setting	5 min / 4300 RPM / 3150 xg 6 min / 4300 RPM / 3150 xg 7 min / 3500 RPM / 2100 xg	4300 / 3150	24	12	6	15 x 17 x 9 in 38.1 x 43.2 x 22.9 cm
DASH Flex 24 00-184-009-000	Horizontal	Digital, 10-Setting	5 min / 4300 RPM / 3150 xg 6 min / 4300 RPM / 3150 xg 7 min / 3500 RPM / 2100 xg	4500 / 3450	24	12	6	15 x 17 x 9 in 38.1 x 43.2 x 22.9 cm

(adapters available for a variety of tube sizes)


**SERO 12 - Blood Banking Centrifuge**  
**A drop-in replacement for the BD SeroFuge**

Model	Rotor Type	Interface	Preset Cycle Time / Speed / RCF	Max Speed RPM / RCF	12 Place Rotor Up to 75mm	6 Place Rotor Up to 100 mm	Dimensions (W x D x H)
SERO 12 00-483-009-001	Fixed Angle	Digital, 10-Setting	15 sec / 3600 RPM / 1040 xg	3600 / 1040	6 capped 12 uncapped	6	13 x 15 x 9 in 33 x 38.1 x 22.9 cm



All centrifuges are available  
for a free 30-day evaluation.  
Visit: [druckerdiagnostics.com/evaluation-program](http://druckerdiagnostics.com/evaluation-program)


**HORIZON Centrifuges**  
**Quality Routine Chemistry**

Model	Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	Up to 16 x 100 mm or 10 mL	Up to 16 x 125 mm or 15 mL	50 mL	Dimensions (W x D x H)
HORIZON 6 00-276-009-000	Horizontal	2-Button, 3-Setting	10 min / 3600 RPM / 1800 xg 15 min / 3300 RPM / 1500 xg 5 min / 1900 RPM / 500 xg	3800 / 2000	6	-	-	12 x 14 x 9 in 30.5 x 35.6 x 22.9 cm
HORIZON 6 FA 00-276-009-001	Fixed Angle	2-Button, 3-Setting	10 min / 3900 RPM / 1600-1850 xg 15 min / 3800 RPM / 1500 xg 5 min / 2200 RPM / 500-600 xg	3900 / 1850	6	6	-	12 x 14 x 9 in 30.5 x 35.6 x 22.9 cm
HORIZON 6 Flex 00-376-009-000	Horizontal	Digital, 10-Setting	10 min / 3600 RPM / 1800 xg 15 min / 3300 RPM / 1500 xg 5 min / 1900 RPM / 500 xg	3800 / 2000	6	-	-	12 x 14 x 9 in 30.5 x 35.6 x 22.9 cm
HORIZON 6 Flex FA 00-376-009-001	Fixed Angle	Digital, 10-Setting	10 min / 3900 RPM / 1600-1850 xg 15 min / 3800 RPM / 1500 xg 5 min / 2200 RPM / 500-600 xg	3900 / 1850	6	6	-	12 x 14 x 9 in 30.5 x 35.6 x 22.9 cm
HORIZON 12 00-238-009-000	Horizontal	2-Button, 3-Setting	10 min / 3500 RPM / 1800 xg 15 min / 3200 RPM / 1500 xg 5 min / 1800 RPM / 500 xg	3700 / 2000	12	-	-	13 x 15 x 9 in 33 x 38.1 x 22.9 cm
HORIZON 12 Flex 00-383-009-000	Horizontal	Digital, 10-Setting	10 min / 3500 RPM / 1800 xg 15 min / 3200 RPM / 1500 xg 5 min / 1800 RPM / 500 xg	3700 / 2000	12	-	-	13 x 15 x 9 in 33 x 38.1 x 22.9 cm
HORIZON 24 00-284-009-000	Horizontal	2-Button, 3-Setting	10 min / 3300 RPM / 1800 xg 15 min / 3000 RPM / 1500 xg 5 min / 1700 RPM / 500 xg	3400 / 2000	24	12	6	15 x 17 x 9 in 38.1 x 43.2 x 22.9 cm
HORIZON 24 Flex 00-384-009-000	Horizontal	Digital, 10-Setting	10 min / 3300 RPM / 1800 xg 15 min / 3000 RPM / 1500 xg 5 min / 1700 RPM / 500 xg	3400 / 2000	24	12	6	15 x 17 x 9 in 38.1 x 43.2 x 22.9 cm

(adapters available for a variety of tube sizes)


**600 Series Centrifuges**  
**Compact Routine Chemistry**

Model	Rotor Type	Interface	Preset Cycle Time / Speed / RCF	Max Speed RPM / RCF	Up to 16 x 100 mm or 10 mL	Up to 16 x 125 mm or 15 mL	50 mL	Dimensions (W x D x H)
614B 00-004-009-001	Fixed Angle	Dial, 1-Setting	1-30 min / 3250 RPM / 1200 xg	3350 / 1300	6	6	-	12 x 14 x 9 in 30.5 x 35.6 x 22.9 cm
642B 00-016-009-001	Horizontal	Dial, 1-Setting	1-30 min / 3380 RPM / 1600 xg	3380 / 1600	6	-	-	12 x 14 x 9 in 30.5 x 35.6 x 22.9 cm
642E 00-018-009-001	Horizontal	2-Button, 1-Setting	10 min / 3380 RPM / 1600 xg	3380 / 1600	6	-	-	12 x 14 x 9 in 30.5 x 35.6 x 22.9 cm
642M 00-077-009-000	Horizontal	2-Button, 1-Setting	10 min / 3400 RPM / 1600 xg	3400 / 1650	6	-	-	12 x 14 x 9 in 30.5 x 35.6 x 22.9 cm

(adapters available for a variety of tube sizes)

**Questions?** Contact Drucker Diagnostics Now.

**TrueBond Animal Health Centrifuges**  
**A centrifuge for every animal health need**


Model	Rotor Type	Interface	Preset Cycle Time / Speed / RCF	Max Speed RPM / RCF	1.5 - 2 mL Fixed Angle Rotor	Microhematocrit HCT Rotor	Dimensions (W x D x H)
TrueBond Duet 00-056-009-000	Dual Rotor	2-Button, 5-Setting	30 sec / 15800 RPM / 12000 xg 1.5 min / 15800 RPM / 12000 xg 2.5 min / 15800 RPM / 12000 xg 45 sec / 9800 RPM / 3900 xg 2 min / 15800 RPM / 13700 xg	15800 / 13700 (microhematocrit)  15800 / 12000 (1.5mL - 2mL)	2	12	7 x 7 x 7 in 17.8 x 17.8 x 17.8 cm

Model	Rotor Type	Interface	Preset Cycle Time / Speed / RCF	Max Speed RPM / RCF	Up to 16 x 100 mm or 10 mL	Up to 16 x 125 mm or 15 mL	Microhematocrit	Dimensions (W x D x H)
TrueBond Set 3 00-276-009-007	Fixed Angle	2-Button, 3-Setting	10 min / 3900 RPM / 1650 xg 5 min / 2000 RPM / 500 xg 6 min / 3800 RPM / 1550 xg	3900 / 1850	6	6	8	12 x 14 x 9 in 30.5 x 35.6 x 22.9 cm
TrueBond 00-376-009-005	Fixed Angle	Digital, 10-Setting	10 min / 3900 RPM / 1650 xg 5 min / 2000 RPM / 500 xg 5 min / 1600 RPM / 300 xg 6 min / 3800 RPM / 1550 xg	3900 / 1850	6	6	8	12 x 14 x 9 in 30.5 x 35.6 x 22.9 cm
TriFLEX In Development	Combination	Digital, 10-Setting	5 min / 3500 RPM / 1500 xg 6 min / 2300 RPM / 660 xg 5 min / 1571 RPM / 300 xg 3 min / 10400 RPM / 12600 xg	10400 / 12600	8 Fixed Angle	8 Fixed Angle	12 Horizontal	15 x 18 x 11 in 38.1 x 45.7 x 27.9 cm

(adapters available for a variety of tube sizes)

**BOOST Centrifuges**  
**Adaptable capacity centrifuges**


Model	Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	Up to 1.9 x 5.4 in (4.8 x 13.7 cm) or 140 grams	Dimensions (W x D x H)
BOOST 2+ Flex 00-783-009-000	Horizontal	Digital, 10-Setting	-	4400 / 3000	2	13 x 15 x 9 in 33 x 38.1 x 22.9 cm
BOOST 4+ Flex 00-389-009-000	Horizontal	Digital, 10-Setting	-	4000 / 2950	4	15 x 17 x 9 in 38.1 x 43.2 x 22.9 cm

Model	Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	Up to 3.6 x 5.4 in (91 x 137 mm) or 330 grams	Dimensions (W x D x H)
BOOST 2+ MAX 00-263-009-000	Horizontal	Digital, 10-Setting	5 min / 3200 RPM / 1800 xg	3200 / 1800	2	15 x 18 x 10 in 38.1 x 45.7 x 25.4 cm

(adapters available for a variety of tube sizes)

**Questions?** Contact Drucker Diagnostics Now.