



## DASH Centrifuges

### High Performance STAT Processing

Model	Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	Up to 13 x 75 mm or 5 mL			Dimensions (W x D x H)
DASH Apex 4 00-053-009-000	Fixed Angle	3-Setting	30 sec / 8500 RPM / 4400 xg 2 min / 8500 RPM / 4400 xg 3 min / 8500 RPM / 4400 xg	8500 / 4440	4			7 x 7 x 7 in 18 x 18 x 18 cm

Model	Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	Up to 16 x 100 mm or 10 mL	Up to 16 x 125 mm or 15 mL	50 mL	Dimensions (W x D x H)
DASH Coag 00-676-009-001	Fixed Angle	3-Setting	2 min / 6600 RPM / 4400 xg 3 min / 6600 RPM / 4400 xg 5 min / 5200 RPM / 2700 xg	6600 / 4400	12	-	-	12 x 14 x 9 in 30 x 36 x 23 cm
DASH Apex 6 00-076-009-004	Horizontal	3-Setting	3 min / 5300 RPM / 4000 xg 5 min / 5300 RPM / 4000 xg 7 min / 3800 RPM / 2000 xg	5300 / 4000	6	-	-	12 x 14 x 9 in 30 x 36 x 23 cm
DASH Flex 6 00-176-009-000	Horizontal	10-Setting, Digital	3 min / 5300 RPM / 4000 xg 5 min / 5300 RPM / 4000 xg 10 min / 3800 RPM / 2000 xg	5300 / 4000	6	-	-	12 x 14 x 9 in 30 x 36 x 23 cm
DASH Apex 12 00-083-009-003	Horizontal	3-Setting	3 min / 5200 RPM / 4000 xg 5 min / 5200 RPM / 4000 xg 7 min / 3600 RPM / 2000 xg	5200 / 4000	12	-	-	13 x 15 x 9 in 33 x 38 x 23 cm
DASH Flex 12 00-183-009-000	Horizontal	10-Setting, Digital	3 min / 5200 RPM / 4000 xg 5 min / 5200 RPM / 4000 xg 7 min / 3600 RPM / 2000 xg	5200 / 4000	12	-	-	13 x 15 x 9 in 33 x 38 x 23 cm
DASH Apex 24 00-084-009-005	Horizontal	3-Setting	5 min / 4300 RPM / 3150 xg 6 min / 4300 RPM / 3150 xg 7 min / 3500 RPM / 2100 xg	4300 / 3150	24	12	6	15 x 17 x 9 in 38 x 43 x 23 cm
DASH Flex 24 00-184-009-000	Horizontal	10-Setting, Digital	5 min / 4300 RPM / 3150 xg 6 min / 4300 RPM / 3150 xg 7 min / 3500 RPM / 2100 xg	4500 / 3450	24	12	6	15 x 17 x 9 in 38 x 43 x 23 cm

(adapters available for a variety of tube sizes)



## SERO 12 - Blood Banking Centrifuge

### A drop-in replacement for the BD SeroFuge

Model	Rotor Type	Interface	Preset Cycle Time / Speed / RCF	Max Speed RPM / RCF	12 Place Rotor Up to 75mm	6 Place Rotor Up to 100 mm	Dimensions (W x D x H)
SERO 12 00-483-009-001	Fixed Angle	10-Setting, Digital	15 sec / 3600 RPM / 1040 xg	3600 / 1040	6 capped 12 uncapped	6	13 x 15 x 9 in 33 x 38 x 23 cm



All centrifuges are available  
for a free 30-day evaluation.  
Visit: [druckerdiagnostics.com/evaluation-program](http://druckerdiagnostics.com/evaluation-program)


**HORIZON Centrifuges**  
**Quality Routine Chemistry**

Model	Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	Up to 16 x 100 mm or 10 mL	Up to 16 x 125 mm or 15 mL	50 mL	Dimensions (W x D x H)
HORIZON 6 00-276-009-000	Horizontal	3-Setting	10 min / 3600 RPM / 1800 xg 15 min / 3300 RPM / 1500 xg 5 min / 1900 RPM / 500 xg	3800 / 2000	6	-	-	12 x 14 x 9 in 30 x 36 x 23 cm
HORIZON 6 FA 00-276-009-001	Fixed Angle	3-Setting	10 min / 3900 RPM / 1600-1850 xg 15 min / 3800 RPM / 1500 xg 5 min / 2200 RPM / 500-600 xg	3900 / 1850	6	6	-	12 x 14 x 9 in 30 x 36 x 23 cm
HORIZON 6 Flex 00-376-009-000	Horizontal	10-Setting, Digital	10 min / 3600 RPM / 1800 xg 15 min / 3300 RPM / 1500 xg 5 min / 1900 RPM / 500 xg	3800 / 2000	6	-	-	12 x 14 x 9 in 30 x 36 x 23 cm
HORIZON 6 Flex FA 00-376-009-001	Fixed Angle	10-Setting, Digital	10 min / 3900 RPM / 1600-1850 xg 15 min / 3800 RPM / 1500 xg 5 min / 2200 RPM / 500-600 xg	3900 / 1850	6	6	-	12 x 14 x 9 in 30 x 36 x 23 cm
HORIZON 12 00-238-009-000	Horizontal	3-Setting	10 min / 3500 RPM / 1800 xg 15 min / 3200 RPM / 1500 xg 5 min / 1800 RPM / 500 xg	3700 / 2000	12	-	-	13 x 15 x 9 in 33 x 38 x 23 cm
HORIZON 12 Flex 00-383-009-000	Horizontal	10-Setting, Digital	10 min / 3500 RPM / 1800 xg 15 min / 3200 RPM / 1500 xg 5 min / 1800 RPM / 500 xg	3700 / 2000	12	-	-	13 x 15 x 9 in 33 x 38 x 23 cm
HORIZON 24 00-284-009-000	Horizontal	3-Setting	10 min / 3300 RPM / 1800 xg 15 min / 3000 RPM / 1500 xg 5 min / 1700 RPM / 500 xg	3400 / 2000	24	12	6	15 x 17 x 9 in 38 x 43 x 23 cm
HORIZON 24 Flex 00-384-009-000	Horizontal	10-Setting, Digital	10 min / 3300 RPM / 1800 xg 15 min / 3000 RPM / 1500 xg 5 min / 1700 RPM / 500 xg	3400 / 2000	24	12	6	15 x 17 x 9 in 38 x 43 x 23 cm

(adapters available for a variety of tube sizes)


**600 Series Centrifuges**  
**Compact Routine Chemistry**

Model	Rotor Type	Interface	Preset Cycle Time / Speed / RCF	Max Speed RPM / RCF	Up to 16 x 100 mm or 10 mL	Up to 16 x 125 mm or 15 mL	50 mL	Dimensions (W x D x H)
614B 00-004-009-001	Fixed Angle	1-Setting, Dial	1-30 min / 3250 RPM / 1200 xg	3250 / 1200	6	6	-	12 x 14 x 9 in 30 x 36 x 23 cm
642B 00-016-009-001	Horizontal	1-Setting, Dial	1-30 min / 3380 RPM / 1600 xg	3380 / 1600	6	-	-	12 x 14 x 9 in 30 x 36 x 23 cm
642E 00-018-009-001	Horizontal	1-Setting	10 min / 3380 RPM / 1600 xg	3380 / 1600	6	-	-	12 x 14 x 9 in 30 x 36 x 23 cm
642M 00-077-009-000	Horizontal	1-Setting	10 min / 3400 RPM / 1600 xg	3400 / 1650	6	-	-	12 x 14 x 9 in 30 x 36 x 23 cm

(adapters available for a variety of tube sizes)

**Questions?** Contact Drucker Diagnostics Now.

## TrueBond Animal Health Centrifuges

### A centrifuge for every animal health need



Model	Rotor Type	Interface	Preset Cycle Time / Speed / RCF	Max Speed RPM / RCF	1.5 - 2 mL Fixed Angle Rotor	Microhematocrit HCT Rotor	Dimensions (W x D x H)
TBD In Development	Combination	5-Setting	30 sec / 15800 RPM / 12000 xg 45 sec / 9800 RPM / 3900 xg 1.5 min / 15800 RPM / 12000 xg 2 min / 15800 RPM / 13700 xg 2.5 min / 15800 RPM / 12000 xg	15800 / 13700 (microhematocrit) 15800 / 12000 (1.5mL - 2mL)	2	12	7 x 7 x 7 in 18 x 18 x 18 cm

Model	Rotor Type	Interface	Preset Cycle Time / Speed / RCF	Max Speed RPM / RCF	Up to 16 x 100 mm or 10 mL	Up to 16 x 125 mm or 15 mL	Microhematocrit	Dimensions (W x D x H)
TrueBond 00-376-009-005	Fixed Angle	10 Setting, Digital	10 min / 3900 RPM / 1650 xg 5 min / 2000 RPM / 500 xg 5 min / 1600 RPM / 300 xg 6 min / 3800 RPM / 1550 xg	3900 / 1850	6	6	8	12 x 14 x 9 in 30 x 36 x 23 cm
TriFLEX Coming Soon	Combination	10-Setting, Digital	5 min / 3500 RPM / 1500 xg 6 min / 2300 RPM / 600 xg 5 min / 1571 RPM / 300 xg 3 min / 10400 RPM / 12600 xg	10400 / 12600	8 Fixed Angle	8 Fixed Angle	12 Horizontal	15 x 18 x 11 in 38 x 46 x 28 cm

(adapters available for a variety of tube sizes)

## BOOST Centrifuges

### Adaptable capacity centrifuges



Model	Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	Up to 1.9 x 5.4 in (4.8 x 13.7 cm) or 140 grams	Dimensions (W x D x H)
BOOST 2+ Flex 00-783-009-000	Horizontal	10-Setting, Digital	-	4400 / 3000	2	13 x 15 x 9 in 33 x 38 x 23 cm
BOOST 4+ Flex 00-389-009-000	Horizontal	10-Setting, Digital	-	4000 / 2950	4	15 x 17 x 10 in 33 x 38 x 25 cm

Model	Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	Up to 3.6 x 5.4 in (91 x 137 mm) or 330 grams	Dimensions (W x D x H)
BOOST 2+ MAX 00-263-009-000	Horizontal	10-Setting, Digital	5 min / 3200 RPM / 1800 xg	3200 / 1800	2	15 x 18 x 10 in 38 x 46 x 25 cm

(adapters available for a variety of tube sizes)

**Questions?** Contact Drucker Diagnostics Now.