

Announcing the TrueBond Duet, our latest and most compact centrifuge for animal health professionals.



Why choose TrueBond Duet instead of StatSpin™ VT?

- **Excellent Quality & Value.** TrueBond Duet combines durable construction with affordability, delivering reliable performance at a great price.
- **Compact & Capable.** TrueBond Duet is our most compact centrifuge for animal health professionals and comes with two rotors to support a variety of tube sizes.
- **Warranty.** TrueBond Duet carries a 2-year overall warranty and calibration guarantee. We also offer a lifetime warranty on all rotors.
- **Customer Service & Tech Support.** TrueBond Duet centrifuges are designed, built, and supported in the USA. Our customer service team is always just a phone call away.

The TrueBond Duet includes a 2-place, fixed angle rotor and a microhematocrit rotor to support the centrifugation of multiple tube sizes.



TrueBond Duet



StatSpin™ VT

Interface	2-Button, 5-Setting	2-Button, 5-Setting
Preset Cycles Time / RPM / RCF	30 sec / 15800 RPM / 12000 xg 1.5 min / 15800 RPM / 12000 xg 2.5 min / 15800 RPM / 12000 xg 45 sec / 9800 RPM / 3900 xg 2 min / 15800 RPM / 13700 xg	30 sec / 15800 RPM / 12000 xg 90 sec / 15800 RPM / 12000 xg 150 sec / 15800 RPM / 12000 xg 45 sec / 9800 RPM / 3900 xg 120 sec / 15800 RPM / 13700 xg
Max Speed RPM / RCF	15800 / 13700 (Microhematocrit) 15800 / 12000 (1.5 - 2 mL)	15800 / 13700
1.5 - 2 mL	2 (Fixed Angle Rotor)	2 (RT12 Rotor)
Microhematocrit (Up to 40 mm)	12 (MHCT Rotor)	12 (RH12 Rotor)
Dimensions (W x H x D)	7 x 7 x 7 in 17.8 x 17.8 x 17.8 cm	6.6 x 8.6 x 6 in 16.8 x 21.8 x 15.2 cm

Why choose TrueBond instead of LW E8?

- Easy to Use & Monitor
- Excellent Quality & Value
- Two Year Warranty
- Unbeatable Customer Service & Tech Support



TrueBond Set 3



LW E8 Combination Variable Speed

Interface	2-Button, 3-Setting	2-Dial
Preset Cycles Time / Speed / RCF	10 min / 3900 RPM / 1650 xg 5 min / 2000 RPM / 425 xg 6 min / 3800 RPM / 1550 xg	N/A
Max Speed RPM / RCF	3900 / 1850	3500 / 1534
Microhematocrit	8	8
Up to 100 mm or 10 mL	6	8
Up to 125 mm or 15 mL	6	8
Dimensions (W x D x H)	12 x 14 x 9 in 30.5 x 35.6 x 22.9 cm	11 x 11 x 9.5 in 27.9 x 27.9 x 24.1 cm



TrueBond



LW E8 Combination Touch

Interface	Digital, 10-Setting	Digital, 10-Setting
Preset Cycles Time / Speed / RCF	10 min / 3900 RPM / 1650 xg 5 min / 2000 RPM / 500 xg 5 min / 1600 RPM / 300 xg 6 min / 3800 RPM / 1550 xg	10 min / 3500 RPM / 1534 xg 5 min / 1800 RPM / 406 xg 6 min / 1500 RPM / 282 xg 6 min / 3500 RPM / 1534 xg
Max Speed RPM / RCF	3900 / 1850	3500 / 1534
Microhematocrit	8	8
Up to 100 mm or 10 mL	6	8
Up to 125 mm or 15 mL	6	8
Dimensions (W x D x H)	12 x 14 x 9 in 30.5 x 35.6 x 22.9 cm	11 x 11 x 9.5 in 27.9 x 27.9 x 24.1 cm



All centrifuges are available for a free 30-day evaluation.
Learn more at: druckerdiagnostics.com/evaluation-program