



Removable Rotors

The TrueBond Duet includes two quick swap rotors, allowing a seamless transition between a 2-place fixed angle rotor (*left*) for 1.5-2 mL blood or urine tubes, to a 12-place 40 mm microhematocrit rotor (*right*).

TrueBond Duet

Compact Dual Rotor Centrifuge

Part # 00-056-009-000

The TrueBond Duet is Drucker Diagnostics' most compact animal health centrifuge, designed to spin microhematocrit tubes, blood, and urine—all in one unit. Its removable rotors allow you to handle a wide variety of veterinary samples with ease.

Easy to Use

The simple two-button interface makes it easy to select a cycle. Use all five presets for routine veterinary testing, or lock to a single cycle for maximum repeatability.

Compact Size

Weighing only 4.3 lbs (1.95 kg) and measuring 7 in x 7 in x 7 in (18 cm x 18 cm x 18 cm), the TrueBond Duet is our smallest veterinary centrifuge.

Safe and Durable

The TrueBond Duet's auto-pop lid locks securely during a run, and pops open automatically when the cycle is done. The brushless motor, reinforced carbon fiber components, and two-year calibration guarantee ensure years of operation with no routine maintenance.

A Great Value

The TrueBond Duet includes an easily swappable fixed angle rotor, microhematocrit rotor, microhematocrit reader card, and a 2-year warranty in the affordable price.

| Applications | Max Speed | Max Capacity | Included | Warranty |
|----------------------------------|---|--|---|--|
| Microhematocrit, Urine, Blood | 15,800 Max RPM 12,000 xg Max RCF (1.5 - 2 mL) 13,700 xg Max RCF (Microhematocrit) | 2 x 1.5 - 2 mL Blood or Urine Tubes 12 x 40mm Microhematocrit Tubes | 2-Place Fixed Angle Rotor, 12-Place Microhematocrit Rotor | 2 years Rotor: lifetime warranty |

Designed, built, and supported in the USA



5 default presets for routine veterinary testing

QR code for easy access to support manuals and more

Select presets using the 2-button interface

Press to select cycle

Free 30-Day Evaluation (U.S. Only)



| Standard Preset Cycles | | Fixed Angle Rotor (1.5 - 2 mL) | MHCT Rotor (Microhematocrit) |
|------------------------|---------------------|-----------------------------------|---------------------------------|
| Quick | 30 sec @ 15800 RPM | 12000 xg | N/A |
| Normal | 1.5 min @ 15800 RPM | 12000 xg | N/A |
| Long | 2.5 min @ 15800 RPM | 12000 xg | N/A |
| Urine | 45 sec @ 9800 RPM | 3900 xg | N/A |
| Microhematocrit | 2 min @ 15800 RPM | N/A | 13700 xg |

| Part Numbers | |
|--------------|---|
| Included | Centrifuge 00-056-009-000 |
| | 2-Place Fixed Angle Rotor 02-001-0-0029 |
| | Microhematocrit Rotor 02-001-0-0030 |
| | Veterinary Microhematocrit Reader Card 03-1-0012-0232 |
| Optional | 1 Year Extended Warranty 03-0-0007-0001 |
| | 2 Year Extended Warranty 03-0-0007-0002 |
| | 3 Year Extended Warranty 03-0-0007-0006 |

| Specifications | |
|-------------------------------|---------------------------------------|
| Max RPM | 15800 RPM |
| Max G-Force (1.5 - 2 mL) | 12000 xg |
| Max G-Force (Microhematocrit) | 13700 xg |
| Dimensions (W x D x H) | 7 x 7 x 7 in 18 x 18 x 18 cm |
| Weight | 4.3 lbs (1.95 kg) |
| Power | 100 - 240 (+/- 10%) VAC - 50/60 Hz |



druckerdiagnostics.com
sales@druckerdiagnostics.com

+1-866-265-1486 (U.S. only)
+1-814-692-7661

Protected by U.S. Patents #6.811.531. #D718,463S #D734,489S Other Patents Pending.