

HORIZON

853VES



HORIZONTAL CLINICAL CENTRIFUGE

12 TUBE, 4,000 RPM, HIGH G-FORCE, MULTI-PURPOSE
FOR REDUCED PROCESSING TIMES AND HIGH-QUALITY ANALYTICAL RESULTS

OVERVIEW

The Model 853VES is a medium capacity, continuous-duty, digitally-controlled centrifuge designed for the separation of fluid samples. The 853VES offers control over almost every aspect of the unit's operation from variable acceleration and deceleration to easy time and speed input. Complete digital controls make it easy to adjust settings and the internal memory allows for common settings to be stored for later use.

APPLICATIONS

The high performance capabilities of the Model 853VES allows it to provide high quality Platelet Poor Plasma (PPP) in as little as 3 minutes, yet it still offers versatility for sensitive urine and fertility samples. The 853VES is also ideal for Platelet Rich Plasma (PRP), Semen, Coagulation, Clinical Chemistry, Urine, and other General Purpose Use.

FEATURES

- Electronic Timer:** Selectable between 0-99 minutes, or hold for continuous operation. Control speed from 500 RPM to maximum
- Variable Acceleration and Deceleration:** Customize entire run
- Capacity:** Up to twelve (12) 1-10 mL tubes with horizontal rotor
- Brushless DC Motor:** Smooth operation with no routine maintenance
- Quiet Operation with Low Vibration:** Double-encased motor assures quiet performance and low out-of-balance vibration
- Footprint:** Compact design uses approximately 1 sq. ft. of counter space
- End of Cycle Alarm:** Audible and visual alarms signal when centrifugation cycle is complete

SAFETY

- Automatic Lid Lock:** Centrifuge will not run with the lid open and the lid cannot be opened while samples are spinning
- Positive Lid Latching:** Firm mechanical latching of the lid prevents the escape of debris in case of tube breakage
- Clear Shatter Proof Lid:** Allows for safe sample observation, optical calibrations, and access for photo tachometer
- Regulatory Approvals:** ETL Compliant to ANSI/UL Standards; CE Marked
- Imbalance Detection:** If an imbalance is detected, the centrifuge will come to a safe, controlled stop
- Welded Steel Construction:** Provides strength and durability for years of use

853VES CENTRIFUGE SPECIFICATIONS

CATALOG NUMBER: 00-054-009-002

Electrical

Voltage 115/230 Volts (± 10%)
 Frequency 50/60 Hz
 Max. Power Requirements 200 Watts
 Protection Breaker 4 Amp. Re-settable
 Centrifuge Motor 1/2 H.P. Brushless DC

Speed Range





Standard Horizontal Rotor 500 to 4,000 RPM

General

Overall Dimensions..... Height..... 8.5 in. (23 cm)
 Width..... 12.5 in. (32 cm)
 Depth..... 15.5 in. (39 cm)
 Weight..... 30 lbs. (13.7 kg)
 Min. Acceleration Time 15 seconds
 Max. Deceleration Time 22 seconds
 Timer Electronic, w/hold or 0 to 99 minutes


Force

Std. Rotor 75 mm Tube Holder 40 to 1,950 xg
 Std. Rotor 100 mm Tube Holder 40 to 2,400 xg
 Std. Rotor 75/100 mm Tube Holder ... 40 to 2,400 xg

Parts Included	QTY Included	Part Number	COMMENTS
 12 Place Horizontal Rotor	1	7786024	High strength glass fiber
 0.5 to 1 mL Tube Adaptor	2	7713068	For use with vials up to 1 mL
 1.5 to 2 mL Tube Adaptor	2	7713065	For use with vials between 1.5 mL and 2 mL
 75 - 100 mm Tube Holder	12	7713079	For use with 75 - 100 mm tubes (3 mL - 10 mL)

Cool Operations


Unique design of the motor housing and rotation chamber allows for cool operation even under the heaviest workloads




2-Stage Horizontal Rotor Included

Our patented swing-out horizontal rotor design incorporates a unique test tube holder that produces the ideal horizontally separated samples

Loading Angle



Rotation Angle



Warranty

The Drucker Diagnostics warrants that this centrifuge is free from defects in workmanship and parts for 2 years.



druckerdiagnostics.com

+1-877-231-3115 (U.S. only)
 +1-814-692-7661