

HORIZON

642VES FIXED



FIXED-ANGLE CLINICAL CENTRIFUGE
6 TUBES PROGRAMMABLE, MULTI-PURPOSE
FOR HIGH-QUALITY ANALYTICAL RESULTS

OVERVIEW

The Model 642VES Fixed-Angle Centrifuge provides the flexibility and performance that clinical laboratories require. The performance of the 642VES Fixed-Angle Centrifuge maximizes sample integrity by keeping patient samples cool during centrifugation. Programmable force (from 250 xg to 1,600 xg) and time settings are simple to use as a digital readout clearly displays the RPM and time settings. The universal power supply and global safety approvals allow the 642VES Fixed-Angle Centrifuge to meet all your global needs.

APPLICATIONS

With its small footprint and moderate price, this centrifuge is ideal for Urine Sedimentation, Platelet Rich Plasma, and other Specialty Applications. Due to the limitations of fixed-angle centrifugation, however, the 642VES Fixed-Angle Centrifuge should only be used for blood separation when centrifuged specimens are not being transported to another site for analysis. Fixed-angle centrifuges produce gel layers that may be susceptible to rupture during transport. These damaged samples cannot be used without an additional centrifugation step; yet, the CLSI recommends against re-centrifugation for its known negative effects on analytical results. For those types of applications, it is best to use the 642VES with a horizontal rotor (Catalog Number: 00-024-009-002). The horizontal rotor is also available, sold separately.

FEATURES

Electronic Timer with Display: Scrollable between 1 and 99 minutes

Capacity: Six (6) tubes from micro tubes (.5 mL) up to 17 mm x 125 mm (15 mL) tubes

Brushless AC Motor: Smooth operation with no routine maintenance

Quiet Operation with Low Vibration: Double-encased motor assures quiet performance and low out-of-balance vibration

Cool Operation: Unique air-flow design cools the rotor chamber and motor with ambient air; protecting your samples and maximizing sample integrity

Footprint: Compact design uses less than 1 sq. ft. of counter space

SAFETY

Automatic Lid Lock: Centrifuge will not run with the lid open and the lid cannot be opened while samples are spinning

Positive Lid Latching: Firm mechanical latching of the lid prevents the escape of debris in case of tube breakage

Clear Shatter Proof Lid: Allows for safe sample observation, optical calibrations, and access for photo tachometer

Global Regulatory Approvals: Certified to US, Canadian, and European Safety standards

Reinforced Guard Bowl: Provides maximum safety and durability

642VES FIXED-ANGLE CENTRIFUGE SPECIFICATIONS




CATALOG NUMBER: 00-024-009-003


General

Overall Dimensions..... Height..... 8.75 in. (22 cm)
 Width..... 11.75 in. (30 cm)
 Depth..... 14.0 in. (35.5 cm)
 Weight..... 12 lbs. (5.4 kg)
 Max. Acceleration Time..... 18 seconds
 Max. Deceleration Time 20 seconds
 Timer Electronic, 1 to 30 minutes,
 preset to 10 minutes, +5% / -2%

Electrical


Voltage..... 120/220 Volts (± 10/25 Volts)
 Frequency 50/60 Hz
 Max. Power Requirements..... 165 Watts
 Protection Breaker..... 4 Amp. Re-settable
 Centrifuge Motor 1/30 H.P. Brushless AC
Speed 1,000 - 3,900 RPM
Maximum Force..... 1,850 xg

Parts Included	QTY Included	Part Number	COMMENTS
 6 Place Fixed-Angle Rotor	1	7786068	High Strength Glass Fiber
 75 - 100 mm Tube Holder	6	7713079	For use with 75 - 100 mm tubes (3 mL - 10 mL)
 125 mm Tube Holder	6	7713032	For use with 125 mm tubes

Optional Accessories	QTY Included	Part Number	COMMENTS
 SmartView™ Platform	Available as an accessory	00-079-009-001	Tilts the centrifuge forward for better view and easier reach inside without loss of g-force.

Cool Operations


Unique design of the motor housing and rotation chamber allows for cool operation even under the heaviest workloads




Fixed-Angle Rotor Included

Used for spinning 75 mm, 100 mm, and 125 mm test tubes in specially designed tube holders

Loading Angle



Rotation Angle



Warranty

The Drucker Diagnostics warranties that this centrifuge is free from defects in workmanship and parts for 2 years.



druckerdiagnostics.com

+1-877-231-3115 (U.S. only)
 +1-814-692-7661