

DASH

6 & 12 STAT CENTRIFUGES

6-Place Cat. No. CA076104, 12-Place Cat. No. CA00717

**Programmable to your
lab's validated cycles**

Lid Lighting Indicates Status
Patent Pending

Simple 2-Button Interface



**Rugged Carbon Fiber
Reinforced Components**

No Routine Maintenance

- Use your validated cycles or the pre-programmed settings for STAT chemistry, coag, and pediatric tubes.
- Easily change settings or lock on a single setting.
- Lid lighting indicates the centrifuge's status (ready, running, done).
- No forgotten tubes in the centrifuge: lid lights keep flashing until the lid is open.
- Universal tube holders accommodate 75 and 100 mm tubes without inserts or spacers.
- Swinging-bucket rotor and tube holders or buckets included.
- 2 year warranty, lifetime rotor warranty.



DASH 6




DASH 12


2-Stage Horizontal Rotor

Our patented swing-out horizontal rotor design incorporates a unique test tube holder that produces the ideal horizontally separated samples.

Loading Angle




Rotation Angle



Cool Operation

Unique design of the motor housing and rotation chamber keeps specimens cool as required by CLSI H21-A5, even under the heaviest workloads.



Factory Settings	DASH 6			DASH 12		
	RPM	Time	G-Force	RPM	Time	G-Force
3 min (5 min for 24)	5,300	3	4,000	5,200	3	4,000
5 min (6 min for 24)	5,300	5	4,000	5,200	5	4,000
Custom	3,800	7	2,000	3,600	7	2,000

Specs	DASH 6	DASH 12
Capacity	6 tubes - 3 to 10 mL	12 tubes - 3 to 10 mL
Height	8 in. (20 cm)	9 in. (23 cm)
Width	11 in. (28 cm)	12.5 in. (32 cm)
Depth	13.5 in. (34 cm)	14.75 in. (37 cm)
Weight	12 lbs. (5.4 kg)	34 lbs. (15 kg)
Max. Acceleration Time	20 seconds	35 seconds
Max. Deceleration Time	20 seconds	40 seconds
Factory Setting Range	1 to 30 minutes, (± 1%)	1 to 30 minutes, (± 1%)
Noise Level	61 dB	61 dB
Voltage	100-240 VAC (± 10%)	100-240 VAC (± 10%)
Frequency	50/60 Hz	50/60 Hz
Power Requirements	220 Watts	230 Watts
Centrifuge Motor	1/2 H.P. Brushless DC	1/2 H.P. Brushless DC
Catalog Number	CA076104	CA00717



LEARN MORE AT [DRUCKERDIAGNOSTICS.COM](https://www.druckerdiagnostics.com)



[druckerdiagnostics.com](https://www.druckerdiagnostics.com)
sales@druckerdiagnostics.com

+1-866-265-1486 (U.S. only)
+1-814-692-7661

Protected by U.S. Patents #6.811.531. #D718,463S #D734,489S Other Patents Pending.