

Top-Load Lockbox



Can pay for itself in one day of bad weather

Heat and cold can both render specimens unusable. If a lab processes at least six samples per day, one day of extreme temperatures without the SampleSafe lockbox could ruin all six samples, at a cost of up to \$350 in re-draws. With a SampleSafe protecting the specimens, no re-draws are required - a \$350 savings, more than double the retail price of the lockbox.

Time to Overheat Comparison

100°F (38°C) Outside Temperature, with Cold Pack




Insulated Steel Box



SampleSafe™ Lockbox

Time to Freezing Comparison

15°F (-9°C) Outside Temperature



Insulated Steel Box



SampleSafe™ Lockbox

TOP LOAD LOCKBOX

Height 13.5 in. / 34.29 cm
 Width 12 in. / 30.48 cm
 Depth 12.5 in. / 31.75 cm
 Weight 8.5 lbs. / 3.85 kg
 Internal Volume 868 in³ / 14,223.97 cm³
 Warranty 5 years





Top Load Lockbox
 P/N: 00-071-009-000

Also available:



Front Load Lockbox
 P/N: 00-078-009-000








Secure anti-theft mounting options (security cable or under door).



Lid can be customized with your logo.

OPTIONAL ACCESSORIES

ANTI-THEFT DEVICES		PART NUMBER
	Under Door Bracket Kit	02-004-0-0002
	Anchor Bracket Kit (Use with Cable)	02-004-0-0003
	Anchor Cable (6 Foot)	03-1-0012-0054
FOR ADDITIONAL PERFORMANCE		PART NUMBER
	False Bottom for Cold Pack	03-1-0012-0039
	Cold Pack (6" x 9" x .8")	03-1-0012-0053