

BOOST Centrifuges
Adaptable capacity centrifuges


Model	Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	Up to 1.9 x 5.4 in (4.8 x 13.7 cm) or 140 grams	Dimensions (W x D x H)
BOOST 2+ Flex 00-783-009-000	Horizontal	10-Setting, Digital	-	4400 / 3000	2	13 x 15 x 9 in 33 x 38 x 23 cm
BOOST 4+ Flex 00-389-009-000	Horizontal	10-Setting, Digital	-	4000 / 2950	4	15 x 17 x 10 in 33 x 38 x 25 cm

(adapters available for a variety of tube sizes)



Model	Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	Up to 3.6 x 5.4 in (91 x 137 mm) or 330 grams	Dimensions (W x D x H)
BOOST 2+ MAX 00-263-009-000	Horizontal	10-Setting, Digital	5 min / 3200 RPM / 1800 xg	3200 / 1800	2	15 x 18 x 10 in 38 x 46 x 25 cm

(adapters available for a variety of tube sizes)



Model	Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	Up to 16 x 100 mm or 10 mL	Up to 16 x 125 mm or 15 mL	Dimensions (W x D x H)
HORIZON 6 Flex FA 00-376-009-001	Fixed Angle	10-Setting, Digital	10 min / 3900 RPM / 1600-1850 xg 15 min / 3800 RPM / 1500 xg 5 min / 2200 RPM / 500-600 xg	3900 / 1850	6	6	12 x 14 x 9 in 30 x 36 x 23 cm

(adapters available for a variety of tube sizes)

Need something different or special? Contact Drucker Diagnostics Now.



All centrifuges are available
for a free 30-day evaluation.
Learn more at: druckerdiagnostics.com/evaluation-program