

Announcing the TrueBond Duet, our latest and most compact centrifuge for animal health professionals.



Why choose TrueBond Duet instead of StatSpin™ VT?

- **Excellent Quality & Value.** TrueBond Duet is built well and affordable.
- **Compact & Capable.** TrueBond Duet is our most compact centrifuge for animal health professionals and comes with two rotors to support a variety of tube sizes.
- **Warranty.** TrueBond Duet carries a 2-year overall warranty and calibration guarantee. We also offer a lifetime warranty on all rotors.
- **Customer Service & Tech Support.** TrueBond Duet centrifuges are designed, built, and supported in the USA. Our customer service team is always just a phone call away.

The TrueBond Duet includes a 2-place, fixed angle rotor and a microhematocrit rotor to support the centrifugation of multiple tube sizes.



TrueBond Duet



StatSpin™ VT

Interface	5-Setting	5-Setting
Preset Cycles Time / RPM / RCF	30 sec / 15800 RPM / 12000 xg 1.5 min / 15800 RPM / 12000 xg 2.5 min / 15800 RPM / 12000 xg 45 sec / 9800 RPM / 3900 xg 2 min / 15800 RPM / 13700 xg	30 sec / 15800 RPM / 12000 xg 90 sec / 15800 RPM / 12000 xg 150 sec / 15800 RPM / 12000 xg 45 sec / 9800 RPM / 3900 xg 120 sec / 15800 RPM / 13700 xg
Max Speed RPM / RCF	15800 / 13700 (Microhematocrit) 15800 / 12000 (1.5 - 2 mL)	15800 / 13700
1.5 - 2 mL	2 (Fixed Angle Rotor)	2 (RT12 Rotor)
Microhematocrit (Up to 40 mm)	12 (MHCT Rotor)	12 (RH12 Rotor)



A family of centrifuges designed for animal health professionals.

TrueBond - Multipurpose Veterinary Centrifuge

PN: 00-376-009-005



Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	Up to 16 x 100 mm or 10 mL	Up to 16 x 125 mm or 15 mL	Microhematocrit	Dimensions (W x D x H)
Fixed Angle	10 Setting, Digital	10 min / 3900 RPM / 1650 xg 5 min / 2000 RPM / 500 xg 5 min / 1600 RPM / 300 xg 6 min / 3800 RPM / 1550 xg	3900 / 1850	6	6	8	12 x 14 x 9 in 30 x 36 x 23 cm

(adapters available for a variety of tube sizes)

TrueBond 2 - Compact Dual Rotor Centrifuge

PN: 00-056-09-000



Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	1.5 - 2 mL Fixed Angle Rotor	Microhematocrit MHCT Rotor	Dimensions (W x D x H)
Dual Rotor	5 Setting	30 sec / 15800 RPM / 12000 xg 1.5 min / 15800 RPM / 12000 xg 2.5 min / 15800 RPM / 12000 xg 45 sec / 9800 RPM / 3900 xg 2 min / 15800 RPM / 13700 xg	15800 / 13700 (microhematocrit) 15800 / 12000 (1.5 mL - 2 mL)	2	12	7 x 7 x 7 in 18 x 18 x 18 cm

TrueBond TriFLEX - Triac Replacement Centrifuge

In Development



Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	Up to 16 x 100 mm or 10 mL	Up to 16 x 125 mm or 15 mL	Microhematocrit	Dimensions (W x D x H)
Combination	10 Setting, Digital	5 min / 3500 RPM / 1500 xg 6 min / 2300 RPM / 600 xg 5 min / 1571 RPM / 300 xg 3 min / 10400 RPM / 12600 xg	10400 / 12600	8 Fixed Angle	8 Fixed Angle	12 Horizontal	15 x 18 x 11 in 38 x 46 x 28 cm

(adapters available for a variety of tube sizes)



All centrifuges are available for a free 30-day evaluation.

Learn more at: druckerdiagnostics.com/evaluation-program



Designed, built, and supported in the USA

+1-866-265-1486 (U.S. only)
+1-814-692-7661

druckerdiagnostics.com
email to: sales@druckerdiagnostics.com