

TrueBond

A centrifuge for every animal health need.

TrueBond Centrifuges Multipurpose Veterinary Processing



Model	Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	Up to 16 x 100 mm or 10 mL	Up to 16 x 125 mm or 15 mL	Microhematocrit	Dimensions (W x D x H)
TrueBond Set 3 00-276-009-007	Fixed Angle	3-Setting	10 min / 3900 RPM / 1650 xg 5 min / 2000 RPM / 425 xg 6 min / 3800 RPM / 1550 xg	3900 / 1850	6	6	8	12 x 14 x 9 in 30 x 36 x 23 cm
TrueBond 00-376-009-005	Fixed Angle	10-Setting, Digital	10 min / 3900 RPM / 1650 xg 5 min / 2000 RPM / 500 xg 5 min / 1600 RPM / 300 xg 6 min / 3800 RPM / 1550 xg	3900 / 1850	6	6	8	12 x 14 x 9 in 30 x 36 x 23 cm

(adapters available for a variety of tube sizes)

TrueBond Duet Compact Dual Rotor Centrifuge



Model	Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	1.5 - 2 mL Fixed Angle Rotor	Microhematocrit MHCT Rotor	Dimensions (W x D x H)
TrueBond Duet 00-056-009-000	Dual Rotor	5 Setting	30 sec / 15800 RPM / 12000 xg 1.5 min / 15800 RPM / 12000 xg 2.5 min / 15800 RPM / 12000 xg 45 sec / 9800 RPM / 3900 xg 2 min / 15800 RPM / 13700 xg	15800 / 13700 (microhematocrit) 15800 / 12000 (1.5 mL - 2 mL)	2	12	7 x 7 x 7 in 18 x 18 x 18 cm

TrueBond TriFLEX Triac Replacement Centrifuge



Model	Rotor Type	Interface	Preset Cycles Time / Speed / RCF	Max Speed RPM / RCF	Up to 16 x 100 mm or 10 mL	Up to 16 x 125 mm or 15 mL	Microhematocrit	Dimensions (W x D x H)
TriFLEX In Development	Combination	10 Setting, Digital	5 min / 3500 RPM / 1500 xg 6 min / 2300 RPM / 600 xg 5 min / 1571 RPM / 300 xg 3 min / 10400 RPM / 12600 xg	10400 / 12600	8 Fixed Angle	8 Fixed Angle	12 Horizontal	15 x 18 x 11 in 38 x 46 x 28 cm

(adapters available for a variety of tube sizes)



All centrifuges are available
for a free 30-day evaluation.
Learn more at: druckerdiagnostics.com/evaluation-program